

Introducing KammRack - Rhino's fastest ever fitting roof rack, joining the new Kamm Generation.

The new KammRack replaces Rhino's AluminiumRack product, which was already a market leading commercial vehicle roof storage system. While at first glance the new rack looks similar to its predecessor, a large number of changes have gone into taking this product to the next level. Most notably, and as implied by the new name, the rack now benefits from the ultra-aerodynamic Kamm bar profile, as well as being Rhino's quickest ever fitting roof rack, requiring only one person to install.

SIDE FRAME

Dimensions

- Total side frame length (L1)
- Nose cone height (H1)
- Side frame height (max.) (H2)
- Side frame width (W1)

Measurements

- 2000mm - 2200mm - 2400mm - 2600mm - 2800mm - 3000mm - 3200mm
- 3600mm - 3800mm - 4000mm - 4200mm - 4400mm - 4800mm
- 140mm
- 161mm
- 64mm

CROSS BARS

Dimensions

- Cross tube length (W2)
- Cross tube height
- Cross tube width
- Leg height - to top of the bar
- Leg height - to bottom of the bar

Measurements

- 1200mm - 1400mm - 1600mm - 1700mm
- 38mm
- 60mm
- 109mm
- 71.5mm

ROLLER

Dimensions

- Length roller (W3)
- Diameter

Measurements

- 1175mm-1325mm-1525mm-1605mm
- 40mm

NEW

KammRack® Black

As part of the launch for KammRack Black, we are proudly working in partnership with the rhino sanctuary Care for Wild. A percentage of all KammRack Black sales will go to supporting this charity's vital conservation work in South Africa.

Scan to find out more:

All-black finish with an aluminium roller.


AERODYNAMIC NOSE CONE

The aerodynamic nose cone provides minimal wind noise and great aesthetics.



AERODYNAMIC CROSS BARS

Our new cross bars provide minimal wind noise, thanks to Rhino's innovative Kamm bar profile.



ALUMINIUM REAR ROLLER

The KammRack rear roller is made from anodised aluminium, which is every bit as strong as its steel predecessor but also fits in better aesthetically with the rest of the rack.



PACKAGING AND SHIPPING

The Rhino KammRack is delivered in just two boxes for most van models, ensuring easy shipping and handling.



QUICK & EASY FITTING PROCESS

KammRack is Rhino's fastest ever fitting roof rack - requiring only one person to install! Scan the QR code to watch our product fitting video with installation times.



SINGLE PERSON INSTALLATION


Thanks to the KammRack's quick and easy installation, with 'click together' side frames and pre-assembled KammBar legs, the rack requires one person to fit.

Installation for one person takes only 25 minutes and 14 minutes for two people.



'CLICK' TOGETHER SIDE FRAMES

Side frames are delivered in two halves for easy shipping, in a single one-man-lift box – the frames are then joined together in seconds during the fitting process.



'CLICK' SIDE FRAME JOINING METHOD


Our innovative method of joining the side frames to the cross tubes takes just a few seconds and a few turns of an allen key to secure.



EASY FIT 'CLICK' TOGETHER REAR ROLLER

The new rear roller clicks into place easily, thanks to two track nuts located in the side frames.



MATERIAL	WHERE USED	ADVANTAGES
Aluminium 6063A T6		
<ul style="list-style-type: none"> - Clear anodised or black powder-coated - Architectural alloy - Thickness 2.4mm 	<ul style="list-style-type: none"> - Side rails - Cross tube - Cross tube saddles 	<ul style="list-style-type: none"> - Extremely durable, high tensile and yield strength - Excellent weight to strength ratio - Scratch resistant - Great for intricate extrusions with a good surface finish and high corrosion resistance
Aluminium 6063 T6		
<ul style="list-style-type: none"> - Clear anodised - Architectural alloy - Thickness 1.5mm 	<ul style="list-style-type: none"> - Rear roller 	<ul style="list-style-type: none"> - Extremely durable, high tensile and yield strength - Excellent weight to strength ratio - Scratch resistant - Great for intricate extrusions with a good surface finish and high corrosion resistance
Composites		
<ul style="list-style-type: none"> - Polymer composite - Glass reinforced - Econyl GF30% 	<ul style="list-style-type: none"> - Side frame connectors - Side frame supports - Cross bar endcaps - Roller endcaps - Roller supports 	<ul style="list-style-type: none"> - Low weight, high strength ratio - High temperature variance - UV resistant
Copolymers		
<ul style="list-style-type: none"> - Polypropylene PPCP - Ducor 2600M 	<ul style="list-style-type: none"> - Nose cones - Leg cowls 	<ul style="list-style-type: none"> - Excellent impact strength - Robust, sturdy design - UV resistant
Electroplated steel		
<ul style="list-style-type: none"> - Trivalent zinc - Electropainted steel 	<ul style="list-style-type: none"> - Endcap tongues - Track nuts - Fitting material (partly) 	<ul style="list-style-type: none"> - High strength - Wear resistant - Corrosion protected
Powder coated steel		
<ul style="list-style-type: none"> - Mild steel - Powder coated black - Textured 	<ul style="list-style-type: none"> - Legs 	<ul style="list-style-type: none"> - High strength - Corrosion protected
Fixings		
<ul style="list-style-type: none"> - Multigrip pop rivets (main connection method) - Bolts & (self locking) nuts size M8, combination of stainless and galvanized steel 		
Tools required for installation 		
<ul style="list-style-type: none"> - 2x allen keys (included) 	<ul style="list-style-type: none"> 2x 10mm/13mm spanners (depending on model) 	<ul style="list-style-type: none"> - 1x ladder

BEACON BRACKET

This bracket is a beacon support that securely holds single & triple bolt fixing beacons in place, increasing the KammRack's functionality. Sold Separately. Part No. FK226



NEW LOAD STOPS

We are also pleased to offer new aerodynamic load stops that are compatible with the KammRack, KammBar Pro and KammBar Fleet. These stylish, modern load stops are available in 1, 2 or 3 pairs. Part No. RLS1 / RLS2 / RLS3

